



"A 100% Employee-Owned Company"

FPP Fuel Oil Pump Package

Designed, Fabricated & Assembled at our facility.

THE FPP FUEL OIL PUMP PACKAGE is designed for transfer applications of No. 2 through No. 6 fuel oil, and capabilities ranging from several gallons per hour to hundreds of gallons per minute. The package is completely pre-piped, (pre-wired), and painted with a high quality rust resistant primer. All isolation valves, check valves, relief/return valves, suction strainer and pressure gauges are included for a completely operational system. The Viking pumps are direct drive, positive displacement, rotary gear type with integral safety relief valves. The unit is completely assembled on a fabricated steel base with a 1" raised lip all around, and is suitably braced for equipment support. Only three connections are required to the package: suction, discharge and return. Control panels are optional.



OUR LOCATIONS

MARYLAND (Corp. Headquarters)

Annapolis Junction

Balt. Phone: (410) 792-4230

Wash. Phone: (301) 953-9370

PENNSYLVANIA

Elizabethtown

Phone: (717) 367-8294

Aston

Phone: (484) 841-6040

VIRGINIA

Ashland

Phone: (804) 550-3311

NEW YORK

Rochester

Phone: (585) 482-9640

Buffalo

Phone: (716) 565-9403

Albany

Phone: (518) 272-3431

FLORIDA

Tampa

Phone: (813) 630-2220

Jacksonville

Phone: (904) 693-2652

OPTIONAL EQUIPMENT

- TEFC Motors
- Manual Motor Starters
- Magnetic Motor Starters
- Demand Alternator
- Run Lights
- UL Labeled Control Panel
- Day Tanks
- Level Control Interface Module**
- Enclosures

Pipes, valves & fittings are USA made.

SCHEDULE

Model	Flow*	Max Discharge Pressure*	Pump Model	HP	RPM	Base Size***	Package Connections	Weight
FPP-60F	60 GPH	100 PSI	F-432	1/4	1200	30 x 30	3/4"	320
FPP-90F	90 GPH	100 PSI	F-432	1/4	1800	30 x 30	3/4"	320
FPP-120FH	120 GPH	100 PSI	FH-432	1/3	1200	30 x 30	3/4"	320
FPP-180FH	180 GPH	100 PSI	FH-432	1/3	1800	30 x 30	3/4"	320
FPP-300G	300 GPH	50 PSI	G-432	1/2	1200	36 x 36	1"	405
FPP-600H	600 GPH	50 PSI	H-432	3/4	1200	36 x 42	1"	425
FPP-1200HL	1200 GPH	50 PSI	HL-432	1-1/2	1200	40 x 42	1-1/2"	485
FPP-420GG	420 GPH	100 PSI	GG-4195	3/4	1200	40 x 42	1"	425
FPP-600GG	600 GPH	100 PSI	GG-4195	1	1800	40 x 42	1"	425
FPP-780HJ	780 GPH	100 PSI	HJ-4195	1-1/2	1200	40 x 46	1-1/2"	500
FPP-1200HJ	1200 GPH	100 PSI	HJ-4195	2	1800	40 x 46	1-1/2"	500
FPP-1800HL	1800 GPH	100 PSI	HL-4195	3	1800	40 x 46	2"	575

* Based on No. 2 Fuel Oil at ambient temperature. Please consult your salesman for conditions other than shown.

** A Level Control Interface Module is required when using a day tank level switch.

*** Do not use for construction. Dimensions are approximate and subject to change. Contact sales for certified dimensions.

Larger capacities available.

Call 1-800-966-1277 or visit Cummins-Wagner.com

